



# DemolClean

Keep your demolition and recycling worksite clean of insulation, polystyrene, plastic etc. with DemolClean, vacuum cleaner for excavators





# DemolClean

DemolClean has been invented by a leading Danish demolition company for their own use. Mr. Toft was very irritated about insulation material flying all over the work sites, and so were the neighbours to the demolition sites when their yard were full of white polystyrene balls.

It is highly costly and dangerous to have people walking around demolition machines, picking up insulation etc.

Hence Mr. Toft made the first DemolClean about three years ago. It took a lot of testing and modifying, but soon four units were in action working well and with excellent results, carrying out the job that Mr. Toft wanted. He saved money on manual cleaning and increased safety on the worksites.

Mr. Toft thought it was such a great tool and felt he wanted to share this with other demolition and recycling companies, hence he asked Østli Attachments to produce and distribute the DemolClean to the rest of the world.

**So here you have it!**



The collector basket is equipped with an outer steel mesh and an easy replaceable filter inside. The bottom hatch opens hydraulically to easy emptying the basket.

The heavy-duty frame is equipped with digging teeth on one side and a cutting edge on the other, to stir in the rubble and cut bigger pieces, so they easily can be sucked in to the shredder wheel.



The heavy-duty shredder wheel is hydraulically driven and shred material like Rockwool, polystyrene, smaller wooden pieces, plastic etc. in to a granulate, and blow it in to the collector basket.

## Technical data:

|   |                            |
|---|----------------------------|
| Weight, excl. bracket                   | 1375 kg                    |
| Dimensions L / H / W                    | 2200 mm/ 2000 mm / 1000 mm |
| Oil requirement                         | 230 l/min @ 250 bar        |
| Max. speed                              | 2800 rpm                   |
| Flow protector valve                    | Standard                   |
| Case drain required, max. back pressure | 1 Bar                      |
| Suction tube size                       | 400 mm                     |
| Volume in collector basket              | 1,2 m <sup>3</sup>         |

See our product video and more on our website: [oestli.dk/demolclean](http://oestli.dk/demolclean)

Contact:



Langelandsvej 25 ● DK-5800 Nyborg ● tlf.: +45 5355 0700 ● [www.oestli.dk](http://www.oestli.dk)