

BREAK TO THE CORE.



FX SERIES Hydraulic hammers



HYDRAULIC HAMMERS

		FX-10	FX-20	FX-30	FX-40	FX-50	FX-70	FX-90
Excavator class ¹	t	0.8 - 1.6	1.5 - 3.0	2 - 4	3 - 5	4 - 7	6 - 9	7 - 12
Weight	kg	100	135	160	195	320	410	550
Height	mm	1180	1210	1240	1280	1580	1683	1950
Blows	bpm	700-1200	700-1200	550-1000	500-800	500-800	400-800	400-700
Working pressure	bar	80-100	100-120	100-120	140-160	140-160	140-160	140-160
Oilflow	l/min	10-20	15-25	25-40	30-50	35-65	40-70	45-85
Chisel diameter	mm	36	45	53	60	68	75	90

HYDRAULIC HAMMERS

		FX-120	FX-160	FX-200	FX-220	FX-340	FX-500
Excavator class ¹	t	10 - 16	14 - 18	16 - 24	19 - 26	28 - 40	42 - 55
Weight	kg	920	1320	1580	1900	2500	4150
Height	mm	2240	2640	2700	2860	3170	3610
Blows	bpm	400-700	400-600	400-600	400-600	300-400	250-350
Working pressure	bar	150-170	150-180	160-180	160-180	160-180	160-180
Oilflow	l/min	80-120	100-140	110-150	130-170	170-230	200-300
Chisel diameter	mm	100	125	135	140	155	175

¹ Recommended excavator / attachment combination

